

Solenvis SL72 Ultrasonic Thickness Gauge

Dynameters Thickness gauge

DYNAMETERS Ultrasonic Thickness gauge is used for measuring the thickness of



materials where access to only one side of the test piece is available for many different materials including steel, cast iron, aluminum, red copper, brass, zinc, quartz glass, polyethylene PVC, gray cast iron, nodular cast iron and other ultrasonic wave well-conductive materials. Dual probe extended your measure range to every possible need in your area. Transducer models are available for special application, including for coarse grain material and high temperature applications. Two-Point Calibration function ; Two work modes: Single point mode and Scan mode ; Coupling status

indicator showing the coupling status ; Auto sleep and auto power off function to conserve battery life.

Features

Large LCD for easy reading

Suitable for all metallic and non-metallic materials

Easy to operate

Wide measuring range from 0.75mm to 300mm (Steel)

Sound Speed Range up to 9999m/s

Display resolution 0.1 mm

Handheld and robust

Function

1. Applicable to measure the thickness of any hard materials, e.g. steel, cast iron, aluminum, red copper, brass, zinc, quartz glass, polyethylene PVC, gray cast iron, nodular cast iron
2. Automatic Zero Adjustment
3. Data Store Function for up to 20 t files (up to 99 values for each file) of stored value
4. Auto Power Shut Off
5. Linear compensation circuit for high accuracy (1%H+0.1)
6. Speed of sound testing (m/s) with 12 storage memory.
7. 2.5 MHz for rough surface measurement

Application

Used for measuring thickness and corrosion of pressure vessels, chemical equipment, boilers, oil storage tanks, etc. Widely used in industries of petroleum, ship building, and machine manufacturing.

Specifications

	DMTG-N(A)	DMTG- H-N(A)
Display	4.5 digits LCD with EL backlight.	128×64 dot matrix LCD with EL backlight.
Measuring Range	0.75 ~ 300mm (in Steel)	
Sound Velocity Range	1000~9999 m/s	
Resolution	0.1mm	0.1/0.01mm (selectable)
Accuracy	± (0.5% Thickness+0.04) mm, depends on materials and conditions	
Units	Metric/Imperial unit selectable	Metric/English unit selectable.
Working Temperature Range	0-45°C & 0-300°C(A) optional	
Reading type	Four measurements readings per second for single point measurement, and ten per second for Scan Mode	
Memory capacity	Memory for up to 20 files (up to 99 values for each file) of stored value	
Communication	N/M	RS232 serial port.
Setting & Alarm	N/M	Upper and lower limit can be pre-set. It will alarm automatically when the result value exceeding the limit
Power Source	Two “AA” size, 1.5 Volt alkaline batteries. 100 hours typical operating time (EL backlight off)	
Outline dimensions	150×74×32 mm	133 X 77 mm.
Weight	245g	345g

DMTG-N(A) Configuration

	No.	Item	Quantity	Remarks
--	-----	------	----------	---------

Standard Configuration	1	Main body	1	
	2	Transducer	1	Model: N05/90°
	3	Couplant	1	
	4	Instrument Case	1	
	5	Operating Manual	1	
	6	Alkaline battery	2	AA size
Optional Configuration	7	Transducer: N02	1	See Appendix A
	8	Transducer: N07	1	
	9	Transducer: HT5	1	

Appendix A: Transducer Selection

Model	Freq MHZ	Diam mm	Measuring Range	Lower limit	Description
N02	2 . 5	14	3.0mm ~ 300.0mm (In Steel)	20	for thick, highly attenuating, or highly scattering materials
N05	5	10	1.2mm ~ 230.0mm (In Steel)	Φ20mm×3.0m m	Normal Measurement
N05 /90°	5	10	1.2mm ~ 230.0mm (In Steel)	Φ20mm×3.0m m	Normal Measurement
N07	7	6	0.75mm ~ 80.0mm (In Steel)	Φ15mm×2.0m m	For thin pipe wall or small curvature pipe wall measurement
DT5	5	12	3 ~ 200mm (In Steel)	30	For high temperature (lower than 300°C) measurement.

Appendix A

DMTG- H-N(A) Configuration

	No.	Item	Quantity	Remarks
Standard Configuration	1	Main body	1	
	2	Transducer	1	Model: N05/90°
	3	Couplant	1	
	4	Instrument Case	1	
	5	Operating Manual	1	
	6	Screwdriver	1	
	7	Alkaline battery	2	AA size
Optional Configuration	8	Transducer: N02		See Appendix B
	9	Transducer: N07		
	10	Transducer: HT5		
	11	Mini thermal printer	1	
	12	Print cable	1	
	13	DataPro for Thickness Gauge	1	For use on the PC
	14	Communication Cable	1	

Appendix B: Transducer Selection

Model	Freq MHZ	Dia. mm	Measuring Range	Lower limit	Description
N02	2	22	3.0mm ~ 300.0mm (In Steel)	20	for thick, highly attenuating, or highly scattering materials
N05	5	10	1.2mm ~ 230.0mm (In Steel)	Φ20mm×3.0mm	Normal Measurement
N05 /90°	5	10	1.2mm ~ 230.0mm (In Steel)	Φ20mm×3.0mm	Normal Measurement
N07	7	6	0.75mm ~ 80.0mm (In Steel)	Φ15mm×2.0mm	For thin pipe wall or small curvature pipe wall measurement
DT5 (DMTG- H-A)	5	12	3 ~ 200mm (In Steel)	30	For high temperature (lower than 300°C) measurement.

Appendix B

Material	Sound Velocity	
	In/us	m/s
Aluminum	0.250	6340-6400
Steel, common	0.233	5920
Steel, stainless	0.226	5740
Brass	0.173	4399
Copper	0.186	4720
Iron	0.233	5930
Cast Iron	0.173-0.229	4400 - 5820
Lead	0.094	2400
Nylon	0.105	2680
Silver	0.142	3607
Gold	0.128	3251
Zinc	0.164	4170
Titanium	0.236	5990
Tin	0.117	2960
Epoxy resin	0.100	2540
Ice	0.157	3988
Nickel	0.222	5639
Flexible glass	0.106	2692
Polystyrene	0.092	2337
Porcelain	0.230	5842
PVC	0.094	2388
Quartz glass	0.222	5639
Rubber, vulcanized	0.091	2311
Teflon	0.056	1422
Water	0.058	1473

DYNAMETERS™

Dynameters Shanghai Co., Ltd
 No.751 Shulin Rd, Eastward New Area,
 Songjiang Industrial Zone,
 Shanghai 201611
 Tel : (+86)21 6760 2289
 Fax :(+86)21 6760 2287
 E-mail: info@dynameters.com
 Web: www.dynameters.com

Solenvis
 experts in energy metering

Solenvis Limited,
 The Peacock Conservatory,
 Weir Bank,
 Bray-on- Thames,
 Berkshire. SL6 2ED United Kingdom
 Tel 01628 762775
 Fax 01628 762763
 Email: sales@solenvisflowmeters.com
 Web: www.solenvisflowmeters.com