

Pressure Reducing Valve PRV

WRAS
APPROVED
PRODUCT



Features

- WRAS Approved Product
- Only 2 PRVs covering four different sizes: 1/2"/ 3/4" and 15mm/22mm
- Less stock items required
- Easily adjustable pressure setting screw
- Inbuilt stainless steel strainer
- Made of DZR to avoid internal corrosion
- Safeguards household fixtures and fittings
- Precision engineered
- Includes pressure setting gauge

Technical Specifications

- Suitable for water temperature up to : 65°C
- Maximum inlet working pressure : 16 bar
- Minimum setting : 1 bar
- Maximum setting : 6 bar
- Pressure gauge connection : 1/4" BSP
- Pressure gauge reading : 0-10 bar / 150psi
- Pre-setting at factory : 3 bar
- Body material : DZR (Chrome)

PRV Care Instructions

Safeguard PRV's are supplied with an inbuilt stainless steel strainer to protect the cartridge from system debris. It is recommended that this filter is periodically cleaned; this can be achieved with the valve in situ.

Procedure: Close both inlet and outlet Isolating valves, if isolating valves are not installed drain the system. Unscrew the Black plastic cap carefully and using pliers pull the complete filter out. Clean with warm water, check and refit the cartridge by pushing back into the body. Re install the plastic cap, spring and adjustment screw. Turn water back on and check pressure setting.

Code Description

| | |
|-------|---|
| 66015 | 1/2" and 3/4" Pressure Reducing Valve (PRV) |
| 66016 | 15mm and 22mm Pressure Reducing Valve (PRV) |